

Installation der Revox-Software auf Topfield-Receivern

Um Topfield-Receiver in das Revox-Multiroom-System integrieren zu können, benötigt man neben dem Communication-Modul mit SAT-Software auch ein spezielles File (DISPLAY.TAP), welches auf die Festplatte des Receivers gespeichert werden muss. Deshalb können nur Topfield-Modelle mit der Endung **PVR (Personal Video Recorder)**, also Geräte mit integrierter Festplatte, verwendet werden. Die Steuerung des Receivers erfolgt über die RS232-Schnittstelle des Communication-Moduls SAT.

Vorgehensweise:

1. Installation des Topfield-Receiver wie in der Bedienungsanleitung beschrieben.
2. Software download von der homepage www.i-topfield.com
Man benötigt das zip-file "windows application setup" aus der Kategorie Support / Software / Topfield-Tools
3. Installieren Sie dieses Programm auf Ihrem Computer.
4. Verbinden Sie den Computer über USB mit dem Topfiel-Receiver und starten Sie ihn.
5. Die Installation des USB-Treibers beginnt
6. Starten Sie das Topfield-Programm **ALTAIR**
7. Erstellen Sie auf der Festplatte des Topfield-Receiver im Hauptverzeichnis *Program Files* ein Unterverzeichnis *Auto Start* - Bitte unbedingt die Schriftweise beachten!
Bei älteren Topfield-Receivern wird dieses Unterverzeichnis durch einen Sendersuchlauf selbstständig generiert.
8. Transferieren Sie das File DISPLAY.TAP von der Festplatte Ihres PCs in den Unterordner *Auto Start* des Topfield-Receiver
9. Bringen Sie den Receiver in Standby und starten Sie ihn erneut.
10. Überprüfen Sie nachträglich im OSD-Menü des Topfield-Receiver, ob das DISPLAY.TAP korrekt im Unterverzeichnis *Auto Start* als *Revox M51 – Topfield Link* installiert wurde – siehe Graphik unten.



Abb.: Hauptverzeichnis **Program Files** mit Unterverzeichnis **Auto Start**, inkl. TAP-File

Installation of Revox-Software on Topfield Receivers

For the integration of Topfield set-top boxes in a Revox Multiroom-System by use of Communicate-Module with SAT-Software on board, it is necessary to copy the Revox file named **DISPLAY.TAP** on the hard disc of that receiver. Thus only Topfield receivers with the extension **PVR (Personal Video Recorder)** can be used, meaning receivers with hard disc. The control takes place via RS232 of the Communication module SAT.

Procedure:

1. Install your Topfield receiver as described in the User's Manual
2. Software download from the homepage www.i-topfield.com
You need the zip-file " windows application setup " from the category Topfield Utilities
3. Install this application on your computer
4. Connect the computer via USB with the Topfield Receiver and start it.
5. The installation of USB-driver starts
6. Start the program **ALTAIR**
7. Generate on the hard disc of the receiver a new subdirectory *Auto Start* within the main directory *Program Files*. Please absolutely consider the writing way of *Auto Start* When using older Topfield receivers, this subdirectory will be generated automatically by carrying out channel search.
8. Now transfer the file **DISPLAY.TAP** from the hard disc of your computer to the subdirectory *Auto Start* of the Topfield receiver.
9. Power down the receiver to Standby and restart it.
10. Check afterwards through the OSD of the Topfield receiver, if the **DISPLAY.TAP** was installed correctly in the subdirectory *Auto Start* as *Revox M51 – Topfield Link*
See also the screen shots below.



Screen shots: Main directory **Program Files** with subdirectory **Auto Start**, incl. **TAP-File**